



## BARRAS HEXAGONALES CALIBRADAS

### DIMENSIONES Y PESOS NOMINALES

SISTEMA INGLES (pulgadas)	CALIDAD	PESO ESTIMADO	
		Kg/m	Kg/6m
11/16	1022	2.07	12.420
3/4	1213 1022	2.47	14.820
13/16	1213 1022	2.9	17.400
7/8	1213 1022	3.36	20.160
15/16	1213 1022	3.86	23.160
1	1213	4.39	26.340
1 1/16	1022	4.95	29.700
1 1/8	1213	5.55	33.300
1 1/4	1213	6.85	41.100
1 3/8	1213 1022	8.29	49.740
1 1/2	1213	9.87	59.220

### TOLERANCIAS DIMENSIONALES

DIAMETRO NOMINAL (d) mm	TOLERANCIA ENTRE CARAS (mms)	TOLERANCIA FUERA DE SECCION (mms)
$6 < d \leq 10$	- 0.09	-0.15
$10 < d \leq 18$	- 0.11	-0.18
$18 < d \leq 30$	- 0.13	-0.21
$30 < d \leq 50$	- 0.16	-0.25
$50 < d \leq 80$	- 0.19	-0.30
$80 < d \leq 120$	- 0.22	-0.35